

Endocoupler

FOCUSABLE ENDOCOUPLER



- Allows the connection of FlexiLux borescopes and fiberscopes to other camera systems with C-mount connection thread
- Suitable for all endoscopes with DIN ocular, without focusing
- Easy to use due to quick snap-lock connection

Item no.

Focal length

TVAD.FOK.F30

f = 30 mm

VARIO ZOOM ENDOCOUPLER



- Stepless image magnification
- Allows the connection of FlexiLux borescopes and fiberscopes to other camera systems with C-mount connection thread
- Suitable for all borescopes and fiberscopes with DIN ocular, with focus
- Parfocal zoom, no re-adjustment of the focus when changing the focal length (zoom)

Item no.

Focal length

TVAD.ZOOM02

f = 18 - 50 mm, parfocal

Full HD Monitor 21.5"

FULL HD MONITOR 21.5"



- For connection to FlexiVision 100
- Display of test results in Full HD

Technical Data

Mains supply	100 - 240 V AC, 50/60 Hz
Background lighting	LED
Resolution	1920 x 1080 Full HD
Image format	16:9
Reaction time	5 ms
Contrast	1000 : 1
Brightness	250 cd/m ²
Viewing angle	170° (H) x 160° (V)
Input signal	HDMI, DVI, VGA, 3G/HD/SD-SDI
Output signal	2 x BNC (CVBS)
Power supply	12 V DC
Operating temperature	-20 °C up to +60 °C
Dimensions	515 x 310 x 50 mm (W x H x D, without foot) 515 x 390 x 182 mm (W x H x D, with foot)
Weight	4.4 kg without foot 5.1 kg (with foot)
Settings	Multilingual On-Screen-Display (OSD)

Item no.

Description

FA.TVMON21.HD	Full HD Monitor 21.5" including foot
---------------	--------------------------------------