

# PTZ60

## Telescopic CCTV Camera

NEW

Suitable for internal video inspection of reactor, boiler, tank, box, bridge box girder and other small entrance, large internal space of the container class device



### Features

**Large touch screen**  
7-inch high-definition touch display with delicate and clear images  
High-definition video recording, photo taking, playback etc.



**1080P**  
66mm diameter 2,000,000 pixels high-definition probe, ten times magnification manual focus, 360° axial rotation



**High brightness lighting**  
Built-in high-brightness LED allows visual inspection in a completely dark environment



**5M**  
5M carbon fiber telescopic pole, the length can be changed from 1.4 to 5m according to the testing conditions.

### Parameters

Controller & Software operation		Color rotation camera	
Controller size	121.4 X 179 X43.6mm	Lens diameter	66mm
Controller weight	0.4kg	Lens length	70mm
LCD display	7-inch LCD display	Pixel	2,000,000
Touchscreen	Capacitive touch screen	Illumination	4 high-brightness LED lights
Resolution	1920X1080	Housing material	Aluminum
Display frame rate	30 frames/second	Radial flip	± 110°
Screen brightness	Adjustable 400cd/m²	Axial rotation	360°
USB interface	USB 2.0 data transfer	DOF	0.5M~∞
Brightness control	Manually adjustable	Image sensor	CMOS
White balance	Manually adjustable	Waterproof standards	IP65
Video output	HDMI HD	Lens operating temperature	-10~50°C
Storage card	64G	System operating temperature	-10~50°C
Image preview magnification	3 times	Storage temperature	-10~50°C
Live image magnification	10 times	AC power input	200V~240V 2A 50/60HZ
lighting control	10 levels of brightness adjustment	DC power input	20V 2A
Image format	JPEG 1920X1080	Lithium electronic battery	20V 2.0Ah
Video format	ASF 1920X1080	Charging time	5 hours
Language	16 languages	Working hour	3 hours

Telescopic pole			
Telescopic rod contraction length	1.4M	Telescopic pole material	Carbon fiber
Telescopic rod expansion length	5M	Weight	3KG (including battery, camera, controller)

